



RAVENOL CVTF NS3/J4 Fluid

RAVENOL CVTF NS3/J4 Fluid is a fully synthetic CVTF (Continuously Variable Transmission Fluid) produced on the basis of PAO with special additives and inhibition which guarantees a perfect function of the CVT transmission.

RAVENOL CVTF NS3/J4 Fluid is a CVTF of the latest generation. It is especially developed for the CVT transmission of JATCO. It guarantees in any mode for maximum wear protection.

RAVENOL CVTF NS3/J4 Fluid is green coloured.

Application Notes

RAVENOL CVTF NS3/J4 Fluid is suitable for use in CVT transmission of following vehicles:

Nissan Qashqai J11 2013-, Nissan Pathfinder R52 2013-, Nissan Altima L33 2013-, Nissan Teana L33 2013-, Nissan Sylphe B17 2012-, Nissan Tiida C12 2014-, Nissan X-Trail T32 2013-, Nissan Elgrand E52 2013-, Nissan Murano Z51 2013-, Nissan Murano Z52 2015-, Mitsubishi Outlander GF7W/8W 2012-, Mitsubishi Delica D5 2012-, Mitsubishi Lancer 2012-, Mitsubishi ASX 2014-, Renault Koleos 2014-, Samsung QM5 2013-, Peugeot 4008 2014-, Citroen C4 Aircross 2014- an others with CVT-transmission JATCO JF016E or JF017E.

Maintenance-filling under normal operating conditions.

Quality Classifications

Practice and tested in aggregates with filling

Nissan KLE53-00004, KLE53-00002, 999MP-NS300P, ATF NS-3. Mitsubishi MZ320261, MZ320262, MZ320288, MZ102658, ATF J4

Characteristic

RAVENOL CVTF NS3/J4 Fluid offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

RAVENOL special fluid is special development for special units and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data.

Please note: RAVENOL special fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct fluid, you can ask your garage or the car dealer with respect to the original OEM type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special fluid can lead to malfunction of the unit and cause failure.

Ravensberger Schmierstoffvertrieb GmbH does not liable for failures in case of wrong selection of RAVENOL special fluid.

Characteristics	Unit	Data	Audit
Colour		green	visual
Density at 20°C	kg/m ³	836	EN ISO 12185
Pourpoint	°C	-57	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

12.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41