

## **RAVENOL Carb Reiniger Spray**

RAVENOL Carb Reiniger Spray is a special high active system cleaner to remove contaminations and deposits in the intake and throttle valve area.

RAVENOL Carb Reiniger Spray has an excellent separation force against oil, grease, rubber, resin and varnish residues.

RAVENOL Carb Reiniger Spray is used for carburetor cleaning and throttle valve cleaning of 2 and 4 stroke gasoline engines.

PAVENOL Carb Reiniger Spray is used for carburetor cleaning and throttle valve cleaning of 2 and 4 stroke gasoline engines.

RAVENOL Carb Reiniger Spray reduces the fuel consumption, improves the motor power, optimises the carburetor power. It is suitable for catalysts. **Application Notes** 

Handling: Spray the parts which have to be cleaned effectually with RAVENOL Carb Reiniger Spray when the motor isn't running. Application time: 2-3 minutes. Then spray RAVENOL Carb Reiniger Spray into the intake and throttle valve area for approximately 30 seconds when the motor is running. Increase the number of revolutions a little bit to burn unfixed deposits.

## Characteristic

RAVENOL Carb Reiniger Spray offers:

- · improves the fuel flow and reduces the fuel consumption
- · excellent cleaning power because of special surface activity
- · improves the motor power
- · optimises the carburetor power
- $\dot{}$  because of the 360° valve system places which are difficult to reach are no problem
- · suitable for catalysts

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

11.02.2016

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther Tel.: 05203/9719-0

Fax.: 052039719-40 / 41