



## RAVENOL Diesel Quality Stabilisator

*Fuel additive for all diesel engines.*

RAVENOL Diesel Quality Stabilisator contains an innovative ingredient, which ensures the general quality of the fuel in diesel fuels.

RAVENOL Diesel Quality Stabilisator improves the storage stability of diesel fuels using effective antioxidants and dispersants.

RAVENOL Diesel Quality Stabilisator enables excellent oxidation protection even at higher temperatures.

RAVENOL Diesel Quality Stabilisator prevents smoke generation and bad smells.

### Application Notes

RAVENOL Diesel Quality Stabilisator is added to the diesel fuel.

Area of application:

- Diesel engines in passenger cars and lorries
- Ensures the quality of the fuel
- For vehicles with longer standstill periods
- Increases the storage stability regarding oxidation and biological contamination

Application: Pour the contents of the container into the full tank. The ideal dosage is a can of RAVENOL Diesel Quality Stabilisator per 40 litres of diesel.

Note: fill the tank completely if the vehicle has not been used for a longer period of time.

### Quality Classifications

RAVENOL Diesel Quality Stabilisator increases the storage stability regarding oxidation and biological contamination using effective antioxidants.

### Characteristic

RAVENOL Diesel Quality Stabilisator provides:

- Improved storage stability of the diesel fuel
- Prevention of microbiological contamination
- Protection against corrosion and deposits in the system
- Improved engine operation and acceleration performance at low outside temperatures
- Prevention of damages to fuel injection system caused by deposits
- Improved winter performance of the fuel

| Characteristics   | Unit               | Data | Audit           |
|-------------------|--------------------|------|-----------------|
| Colour            |                    | gelb | visual          |
| Density at 20°C   | kg/m <sup>3</sup>  | 850  | EN ISO 12185    |
| Viscosity at 40°C | mm <sup>2</sup> /s | 7    | DIN EN ISO 3104 |
| Flash Point PM    | °C                 | 65   | DIN ISO 3679    |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

15.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41