

RAVENOL Feinmechaniköl

RAVENOL Feinmechaniköl is a multi-purpose, universal mechanics oil which is formulated to be resin and acid -free.

Application Notes

RAVENOL Feinmechaniköl can be used as a universal general purpose oil both in the home and out for bicycles, sewing machines, household and office equipment, locks, tools, cars, motorcycles, hobby work etc. and anywhere that this type of multi-purpose oil is required.

Characteristic

RAVENOL Feinmechaniköl is characterized by its light color, mild odor and a low sulphur content, making it pleasant in use. It is formulated to offer a long-lasting effect with little or no aging effect, and has a good viscosity-temperature behaviour making it suitable for use across a wide temperature range.

| Characteristics | Unit | Data | Audit |
|--------------------|-------|------|--------------|
| Colour | | hell | visual |
| Density at 20°C | kg/m³ | 859 | EN ISO 12185 |
| Viscosity at 40°C | mm²/s | 22,5 | DIN 51 562 |
| Viscosity at 100°C | mm²/s | 4,5 | DIN 51562 |
| Viscosity index VI | | 112 | DIN ISO 2909 |
| Flash point (COC) | °C | 224 | DIN ISO 2592 |
| Pourpoint | °C | -15 | DIN ISO 3016 |
| | | | |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

01.03.2016 Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther Tel.: 05203/9719-0 Fax.: 052039719-40 / 41