



RAVENOL Fließverbesserer

RAVENOL Fließverbesserer can be mixed and is compatible with all diesel fuels (except Biodiesel) as well as fuel oils EL. Higher dosings as recommended are harmless. Demixing won't occur.

Practical experiences show that under consideration of the different kind of diesel fuels and fuel oils EL offered on the market following cold properties are given.

Application Notes

	Addition: Liter Ravenol Fließverbesserer to Liter Diesel fuel respectively fuel oil EL	Operating temperature
Summer-Diesel fuel as well as fuel oil EL	1 : 1000 *)	- 10°C
	2 : 1000	- 18°C
	3 : 1000	- 23°C
	4 : 1000	- 25°C
Winter-Diesel-fuel	1 : 1000	- 25°C
	2 : 1000	- 28°C
	3 : 1000	- 31°C

Characteristic

The basic advantages of RAVENOL Fließverbesserer are:

- complete restless burning
- no erosion of the flammability
- no change of the hazard category
- no reduction of the viscosity, no illegal wastage in the pump

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

27.05.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41