



RAVENOL Getriebeöl CLP 320

RAVENOL Getriebeöl CLP 320 is high-grade industrial gear oil, based on mineral oil, formulated with lead-free EP-additives. Due to its special combination a very good, stable high-pressure absorption is achieved for shock load.

RAVENOL Getriebeöl CLP 320 has a low pour point and therefore very good low temperature properties.

Application Notes

RAVENOL Getriebeöl CLP 320 is to be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.

Quality Classifications

Specifications

FZG 12, Vickers Vane Pump, DIN 51 517 Part 3, US Steel 224, Eickhoff Bergbautechnik Bestätigung für die Verwendung in den Getrieberäumen

Characteristic

RAVENOL Getriebeöl CLP 320 offers:

- a very good resistance towards high pressures and hock loads
- a good resistance against high temperatures
- good corrosion preventing properties
- an excellent prevention from wear
- a very good activity against foaming
- a low pour point

Characteristics	Unit	Data	Audit
Colour		braun	visual
Density at 20°C	kg/m ³	904	DIN 51 757
Viscosity at 40°C	mm ² /s	320,0	DIN 51 562
Viscosity at 100°C	mm ² /s	23,5	DIN 51 562
Viscosity index VI		92	DIN ISO 2909
Flash point (COC)	°C	230	DIN ISO 2592
Pourpoint	°C	-15	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

22.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41