

RAVENOL HJC - Protect FL22 HOT CLIMATE -15°C

AMINE - SILICATE - FREE

RAVENOL HJC Hybrid Japanese Coolant HOT CLIMATE -15°C is a ready-to-use, prediluted with water, ethylene-glycol based and time-tested coolant without amine and silicates. This product is formulated based on a proven inhibitor development as an extended life radiator antifreeze.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject coolant to lengthy corrosion and cavitation tests.

Application Notes

RAVENOL HJC Hybrid Japanese Coolant HOT CLIMATE -15°C is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add RAVENOL HJC Hybrid Japanese Coolant HOT CLIMATE -15°C to radiator to fill line.

Quality Classifications

RAVENOL HJC Hybrid Japanese Coolant HOT CLIMATE -15°C is tried and tested for aggregates specifying:

Specifications

MAZDA FL22 Coolant, FORD WSSM97B55 (Motocraft Speciality Green Engine Coolant), FORD VC-10-A2, Nissan Anti-freeze Coolant (L250), Nissan KE90299934, KE90299944, Nissan KLD4100002EU, KLD41-00002, 999MP-GTRT00P, Hyundai Long Life Coolant, Hyundai 07100-00200, 07100-00400, 00232-19010, Mazda 000077508E20, C122CL005A4X, C100CL005A4X

Characteristic

RAVENOL HJC Hybrid Japanese Coolant HOT CLIMATE -15°C offers:

- Excellent for aluminium alloy engines
- Good reserve alkalinity
- Premium corrosion additives for optimal rust protection
- · Compatible with elastomers used in automotive radiators

Characteristics	Unit	Data	Audit	
Colour		grün	visual	
Density at 20°C	kg/m³	1047	EN ISO 12185	
pH-Value		7,8	ASTM D 1287	
Freezing point	°C	−15°C	ASTM D 1177	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

28.01.2016

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther

Tel.: 05203/9719-0 Fax.: 052039719-40 / 41