



## RAVENOL HJC - Protect FL22 Premix -40°C

AMINE - SILICATE - FREE

RAVENOL HJC Hybrid Japanese Coolant Premix -40°C is a ready to use, prediluted with water, ethylene-glycol based and time-tested coolant without phosphates, nitrites, amines and silicate. This product is formulated based on a proven inhibitor development as an extended life radiator antifreeze.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection.

That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

RAVENOL HJC Hybrid Japanese Coolant Premix -40°C protects the cooling system from rust, frost, and in summer, from overheating.

### Application Notes

RAVENOL HJC Hybrid Japanese Coolant Premix -40°C is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Add RAVENOL HJC Hybrid Japanese Coolant Premix -40°C to radiator to fill line.

### Quality Classifications

RAVENOL HJC Hybrid Japanese Coolant Premix -40°C is tried and tested for aggregates specifying:

#### **Specifications**

MAZDA FL22 Coolant, FORD WSSM97B55 (Motocraft Speciality Green Engine Coolant), FORD VC-10-A2, Nissan Anti-freeze Coolant (L250), Nissan KE90299934, KE90299944, Nissan KLD4100002EU, KLD41-00002, 999MP-GTRT00P, Hyundai Long Life Coolant, Hyundai 07100-00200, 07100-00400, 00232-19010, Mazda 000077508E20, C122CL005A4X, C100CL005A4X

### Characteristic

RAVENOL HJC Hybrid Japanese Coolant Premix -40°C offers:

- Excellent for light metal engines
- Good reserve alkalinity
- High-quality corrosion additives for optimal corrosion protection
- Elastomer compatible with elastomers used in automotive radiators

Characteristics	Unit	Data	Audit
Colour		grün	visual
Density at 20°C	kg/m <sup>3</sup>	1082	EN ISO 12185
pH-Value		7,8	ASTM D 1287
Freezing point	°C	-40°C	ASTM D 1177

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

27.01.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41