



RAVENOL SNOWMOBILES Fullsynth. 2-Takt

RAVENOL SNOWMOBILES Fullsynth. 2-Takt is high quality blue coloured fully synthetic two-stroke engine oil with special esters and Polyisobutylene (PIB) specifically formulated for use in snowmobiles.

RAVENOL SNOWMOBILES Fullsynth. 2-Takt is based on synthetic base oils with effectively low ash additives.

Application Notes

RAVENOL SNOWMOBILES Fullsynth. 2-Takt can generally be mixed with regular petrol 1:100.

RAVENOL SNOWMOBILES Fullsynth. 2-Takt is used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load.

RAVENOL SNOWMOBILES Fullsynth. 2-Takt is also suitable for the lubrication of two stroke scooters with water cooling.

Quality Classifications

Specifications

API TD, ISO-L-EGD

Approvals

Erfüllt: JASO FD, Freigabe JASO 049RAV154

Practice and tested in aggregates with filling

For use in vehicles of Yamaha, Suzuki, Bombardier, Kawasaki, Arctic Cat, Rotax 253

Characteristic

RAVENOL SNOWMOBILES Fullsynth. 2-Takt offers:

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- Clean spark plugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion

Characteristics	Unit	Data	Audit
Colour		blue	visual
Density at 20°C	kg/m ³	869	EN ISO 12185
Viscosity at 40°C	mm ² /s	48,0	DIN 51 562
Viscosity at 100°C	mm ² /s	8,0	DIN 51 562
Viscosity index VI		138	DIN ISO 2909
Pourpoint	°C	-42	DIN ISO 3016
TBN	mg KOH/g	2,4	DIN ISO 3771
Sulphated ash	%wt.	0,04	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

14.11.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41