



RAVENOL SNOWMOBILES Mineral 2-Takt

RAVENOL SNOWMOBILES Mineral 2-Takt is high quality 2-stroke engine oil based on mineral base oils with an ash less additive package for optimum lubricity and excellent corrosion protection.

Application Notes

RAVENOL SNOWMOBILES Mineral 2-Takt is recommended for typical mixing ratio: 1: 50

RAVENOL SNOWMOBILES Mineral 2-Takt is particularly suitable for remote lubrication and self-mixing systems. The usage in separate lubrication systems with this product will ensure optimum lubrication and minimizes smoke environmentally friendly.

RAVENOL SNOWMOBILES Mineral 2-Takt is ideal for lubricating two-stroke snowmobiles with suitable water cooling.

RAVENOL SNOWMOBILES Mineral 2-Takt is an especially developed high performance engine oil, suitable for use in self-mixing SNOW MOBILE for both air-cooled as well as for water-cooled two-stroke gasoline engines.

Quality Classifications

RAVENOL SNOWMOBILES Mineral 2-Takt Mineral corresponds and fulfils the following specifications respectively classifications:

Specifications

API TB, ISO-L-EGB

Approvals

JASO FB 049RAV157

Practice and tested in aggregates with filling

Suzuki, Kawasaki, Arctic Cat, Yamaha, Bombardier, Ski-Doo, Polaris

Characteristic

RAVENOL SNOWMOBILES Mineral 2-Takt offers:

- An excellent corrosion protection in all oil-wetted engine parts
- Immediate, homogeneous mixture with the used fuel (including lead-free)
- An effective pressure and temperature resistant oil film
- An excellent anti-wear performance
- A clean burning with no deposits
- Low coking
- High wear protection

Characteristics	Unit	Data	Audit
Colour		blau	-
Density at 20°C	kg/m ³	872	EN ISO 12185
Viscosity at 40°C	mm ² /s	70,0	DIN 51 562
Viscosity at 100°C	mm ² /s	9,7	DIN 51 562
Viscosity index VI		118	DIN ISO 2909
Pourpoint	°C	-24	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

16.02.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41