



RAVENOL Standard Truck SAE 40

RAVENOL Standard Truck SAE 40 is mineral mono grade motor oil for trucks. All-season oil for all truck diesel engine types. High protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.

Application Notes

RAVENOL Standard Truck SAE 40 is mono grade motor oil for use in truck diesel engines. Also suitable for stationary plants.

Specifications

API CD, ACEA E2/B4

Approvals

MTU Typ 1(DDC BR 2000 u. 4000)

Practice and tested in aggregates with filling

MB 228.0, MAN 270, Voith Retarder A, Voith DIWA ZF TE-ML 02C/03B/04B/06A/07D

Characteristic

RAVENOL Standard Truck SAE 40 offers:

- Good shear stability
- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts

Characteristics	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 20°C	kg/m ³	892	EN ISO 12185
Viscosity at 40°C	mm ² /s	160,0	DIN 51 562
Viscosity at 100°C	mm ² /s	15,2	DIN 51 562
Viscosity index VI		100	DIN ISO 2909
Flash point (COC)	°C	225	DIN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016
TBN	mg KOH/g	10,1	DIN ISO 3771
Sulphated ash	%wt.	1,17	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

09.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41