



RAVENOL Super HD 30

RAVENOL Super HD 30 is a mineral multigrade engine oil for passenger car gasoline and diesel engines with and without turbocharging, and is also suitable for commercial vehicle engines and vans under light loads which require this grade of oil.

Designed to minimize friction and wear, the formulation ensures year round high lubricity throughout all operating conditions. Extended oil drain capability where recommended by the vehicle manufacturer.

Application Notes

RAVENOL Super HD 30 is suitable for both gasoline and diesel engines in cars, van and commercial vehicles which require this grade of engine oil.

Specifications

API CD/SF

Practice and tested in aggregates with filling

MIL-L-46152 B, MIL-L-2104 D MB 227.0, CCMC G4 (gültig bis 31.12.96)

Characteristic

RAVENOL Super HD 30 offers:

- Corrosion protection
- Good shear stability
- High oxidation stability
- Excellent viscosity-temperature behavior
- Enhanced levels of detergent and dispersant for cleaner engines
- Very good cold starting properties
- Prevents formation of deposits and black sludge

Characteristics	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 20°C	kg/m³	890,3	EN ISO 12185
Viscosity at 40°C	mm²/s	112,9	DIN 51 562
Viscosity at 100°C	mm²/s	12,1	DIN 51 562
Viscosity index VI		96	DIN ISO 2909
Flash point (COC)	°C	263	DIN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016
TBN	mg KOH/g	5,5	DIN ISO 3771

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

12.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41