



RAVENOL Turbinenöl T 68

RAVENOL Turbinenöl T 68 is produced for the lubrication of gas and steam turbines as well as turbo compressors with and without transmission according to the specifications of DIN 51 515-2.

RAVENOL Turbinenöl T 68 is based on high quality mineral base oils with agents to increase the corrosion protection and aging resistance.

Application Notes

RAVENOL Turbinenöl T 68 is used in fixed gas and steam turbines as well as electrical machines or machines driven by steam turbines like generators, compressors, pumps and transmissions.

RAVENOL Turbinenöl T 68 can also be used for the lubrication of hydraulic systems, compressors, gear transfers and bearings in case of problems of the contamination with water because a high protection against rust and oxidation is requested.

Quality Classifications

RAVENOL Turbinenöl T 68 corresponds to:

Specifications

BS 489, DIN 51515 (L-TD), ISO 6743/0

Characteristic

RAVENOL Turbinenöl T 68 is an universal mineral oil for turbines of especially chosen refined base oils with a natural high viscosity index. So-called "metal deactivators" are added to the turbine oil in addition to the normal additives in order to guarantee the following characteristics:

- an excellent thermic and oxidative stability
- an excellent viscosity temperature behaviour
- a high and stable viscosity index
- a very good oxidation stability also at very high temperatures
- a good protection against corrosion of Ferro and non Ferro metals
- an excellent water separation behaviour
- a very good air separation behaviour which excludes foam formation as far as possible
- a low pour point
- a good corrosion behaviour
- an excellent water separation behaviour / demulsifying behaviour

Characteristics	Unit	Data	Audit
Density at 20°C	kg/m ³	876	EN ISO 12185
Viscosity at 40°C	mm ² /s	68	DIN 51 562
Viscosity at 100°C	mm ² /s	8,6	DIN 51 562
Viscosity index VI		98	DIN ISO 2909
Flash point (COC)	°C	220	DIN ISO 2592
Pourpoint	°C	-25	DIN ISO 3016
Acid number	mg KOH/g	0,15	-

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

16.02.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41