



RAVENOL Turbo Plus SHPD SAE 10W-30

RAVENOL Turbo Plus SHPD 10W-30 is high performance multi-grade oil for use in petrol and diesel engines including turbo versions.

RAVENOL Turbo Plus SHPD 10W30 meets the requirements of SAE-Class 10W-30. This adjustment of viscosity also ensures a good lubricating film at high temperatures.

Application Notes

RAVENOL Turbo Plus SHPD 10W-30 is particularly suitable for engines with already high performance.

Quality Classifications

Specifications

API CI-4/SL, ACEA E7, A3/B4

Approvals

YaMZ

Practice and tested in aggregates with filling

Volvo VDS 3, MTU Type 3, Renault RLD, Cummins CES 20071, 72, 76, 77, Caterpillar TO-2, MB 228.3, MAN M 3275

Characteristic

RAVENOL Turbo Plus SHPD 10W-30 offers:

- Very good shear stability
- An excellent viscosity-temperature behaviour
- Conclusive detergent- and dispersant properties
- High security reserves also under limited lubrication circumstances
- very good cold starting properties
- Prevents black sludge formation
- Suitable for catalyst-equipped vehicles

Characteristics	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 20°C	kg/m ³	871	EN ISO 12185
Viscosity at 40°C	mm ² /s	73,7	DIN 51 562
Viscosity at 100°C	mm ² /s	11,2	DIN 51 562
Viscosity index VI		143	DIN ISO 2909
Flash point (COC)	°C	216	DIN ISO 2592
Pourpoint	°C	-34	DIN ISO 3016
TBN	mg KOH/g	11,5	DIN ISO 3771
Sulphated ash	%wt.	1,2	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

09.11.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41