



RAVENOL VDL SAE 5W-40

Diesel-Fullsynth

RAVENOL VDL SAE 5W-40 is synthetic engine oil, which allows the fuel efficient engines operation. RAVENOL VDL SAE 5W-40, a reliable and a heavy-duty engine oil of EC-category (Energy Conserving) is based on synthesis technology in order to guarantee the low viscosity of SAE-category 5W as well as the low evaporation loss at the same time.

RAVENOL VDL SAE 5W-40 corresponds the high-tech-requirements of powerful engine generation.

Application Notes

RAVENOL VDL SAE 5W-40 is suitable for the fuel efficient all year use in all modern gasoline and passenger car diesel engines and is developed special for turbo charger- and catalyst operation.

RAVENOL VDL SAE 5W-40 guarantees operation safety in all driving conditions as for example the extremely stop-and-go traffic as well as high-speed-highway driving.

Specifications

API CF, ACEA B3/B4

Practice and tested in aggregates with filling

VW 505 00, BMW Longlife-98, MB 229.3, Opel GM-LL-B-025, TOYOTA Common Rail, Mitsubishi, NISSAN, Fiat 9.55535-M2

Characteristic

RAVENOL VDL SAE 5W-40 offers:

- High abrasion resistance
- Fuel economy by low friction property
- Excellent detergent and dispersant property
- Prevention of black sludge formation
- Extended endurance because of oxidation stability
- Excellent cold start characteristics
- Excellent viscosity-temperature- characteristics
- Low evaporation tendency
- Suitable for catalysts

Characteristics	Unit	Data	Audit
Colour		braun	visual
Density at 20°C	kg/m ³	850	EN ISO 12185
Viscosity at 40°C	mm ² /s	83,0	DIN 51 562
Viscosity at 100°C	mm ² /s	13,8	DIN 51 562
Viscosity index VI		163	DIN ISO 2909
Flash point (COC)	°C	227	DIN ISO 2592
Pourpoint	°C	-39	DIN ISO 3016
TBN	mg KOH/g	8,4	DIN ISO 3771
Sulphated ash	%wt.	1,0	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

22.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41