



RAVENOL VMS SAE 5W-30

RAVENOL VMS SAE 5W-30 is fully synthetic low friction motor oil with CleanSynto® technology for Daimler passenger car petrol and diesel engines with and without turbo-charging and direct injection. Minimisation of friction, abrasion and fuel consumption, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations. The excellent cold start characteristics provide optimal lubricant safety in the cold-running phase. Because of the noticeable fuel economy RAVENOL VMS SAE 5W-30 contributes the reduction of pollutant emissions and protecting the environment. RAVENOL VMS SAE 5W-30 is Oil which prevents effectively the reset of the diesel soot particulate filter.

Application Notes

RAVENOL VMS SAE 5W-30 is suitable for demanding motors as high performance low friction multi-grade gear oil. It is recommended for all modern passenger car gasoline and diesel engines, including turbo versions, for direct injection motors and it is also recommended for all operation conditions. RAVENOL VMS SAE 5W-30 is recommended for use in vehicles with diesel particulate filters. It is especially formulated according to the Daimler Low SPASh multigrade service engine oil specification MB 229.52 and suitable for BlueTEC OM642.

Specifications

API SN, ACEA C3

Practice and tested in aggregates with filling

MB 229.52, MB 229.51, MB 229.31, Chrysler MS-11116

Characteristic

RAVENOL VMS SAE 5W-30 offers:

- Noticeable Fuel-Economy (FE)
- Low evaporation loss
- Excellent detergent and dispersant property
- Prevention of black sludge formation
- Improved cleaner engine
- Extended endurance because of oxidation stability
- Excellent cold start characteristics even at temperatures of below -30°C
- Excellent viscosity-temperature-characteristics
- Low evaporation tendency
- Suitable for catalysts
- Prevents effectively the reset of the diesel soot particulate filter

Characteristics	Unit	Data	Audit
Colour		braun	visual
Density at 20°C	kg/m ³	844	EN ISO 12185
Viscosity at 40°C	mm ² /s	71,6	DIN 51 562
Viscosity at 100°C	mm ² /s	12,3	DIN 51 562
Viscosity index VI		171	DIN ISO 2909
Flash point (COC)	°C	236	DIN ISO 2592
Pourpoint	°C	-42	DIN ISO 3016
TBN	mg KOH/g	8,1	DIN ISO 3771

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

14.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41