

RAVENOL WATERCRAFT Fullsynth. 2-Takt

RAVENOL WATERCRAFT Fullsynth. 2-Takt is high quality blue coloured fully synthetic two-stroke engine oil. RAVENOL WATERCRAFT Fullsynth. 2-Takt is based on polyolester with special esters and Polyisobutylene (PIB) and effectively two stroke additives.

 $\textbf{RAVENOL WATERCRAFT Full synth. 2-Takt} \ is \ especially \ developes for \ two \ stroke \ engines \ in \ water \ vehicles.$

Application Notes

RAVENOL WATERCRAFT Fullsynth. 2-Takt can generally be mixed with regular petrol 1:100.

RAVENOL WATERCRAFT Fullsynth. 2-Takt is used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load.

RAVENOL WATERCRAFT Fullsynth. 2-Takt is also suitable for the lubrication of two stroke scooters with water cooling.

Quality Classifications

RAVENOL WATERCRAFT Fullsynth. 2-Takt is approved, tried and tested for aggregates specifying:

Specifications

API TD, ISO-L-EGD, JASO FD

Approvals

NMMA TC-W3®, RL-29019G

Characteristic

RAVENOL WATERCRAFT Fullsynth. 2-Takt offers:

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- Clean spark plugs provide optimal performance of the engines
- · A very high wear and corrosion protection
- Low exhaust emission levels by good combustion

| Characteristics | Unit | Data | Audit |
|--------------------|----------|-------|--------------|
| Colour | | blue | visual |
| Density at 20°C | kg/m³ | 869 | EN ISO 12185 |
| Viscosity at 40°C | mm²/s | 48,0 | DIN 51 562 |
| Viscosity at 100°C | mm²/s | 8,0 | DIN 51 562 |
| Viscosity index VI | | 138 | DIN ISO 2909 |
| Pourpoint | °C | - 21 | DIN ISO 3016 |
| Sulphated ash | %wt. | <0,04 | - |
| TBN | mg KOH/g | 2,4 | DIN ISO 3771 |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

09.03.2016

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther

Tel.: 05203/9719-0 Fax.: 052039719-40 / 41