



RAVENOL WATERCRAFT Teilsynth. 2-Takt

RAVENOL WATERCRAFT Teilsynth. 2-Takt is a semi-synthetic 2-stroke oil, dyed blue, with special esters and Polyisobutylene (PIB) on the basis of selected, high quality base oils and an ash-free additive package for optimum viscosity and corrosion protection.

Application Notes

RAVENOL WATERCRAFT Teilsynth. 2-Takt can be used in a mixture of up to 1:75 with regular petrol.

RAVENOL WATERCRAFT Teilsynth. 2-Takt is particularly suitable for the lubrication of air-cooled two-stroke petrol engines with high engine speeds and severe loads.

RAVENOL WATERCRAFT Teilsynth. 2-Takt is excellently suited for the lubrication of two-stroke watercrafts with water cooling systems.

RAVENOL WATERCRAFT Teilsynth. 2-Takt meets the requirements of the National Marine Manufacturers' Association NMMA TC-W3 (Yamaha CE 50S, Mercury).

Quality Classifications

RAVENOL WATERCRAFT Teilsynth. 2-Takt is tried and tested in aggregates with filling instruction:

Specifications

API TC, ISO-L-EGC, JASO FC

Approvals

NMMA TC-W3®, RL-30010H

Characteristic

RAVENOL WATERCRAFT Teilsynth. 2-Takt offers:

- Excellent lubrication of all engine parts
- A powerful cleaning performance, which keeps combustion chambers as well as intake and exhaust channels free of combustion residue and deposits to the greatest possible extent
- Clean spark plugs provide for an optimum performance of the engine
- Great wear and corrosion protection
- Low vehicle exhaust emission due to good combustion

Characteristics	Unit	Data	Audit
Colour		blau	visual
Density at 20°C	kg/m ³	874	EN ISO 12185
Viscosity at 40°C	mm ² /s	65,0	DIN 51 562
Viscosity at 100°C	mm ² /s	9,5	DIN 51 562
Viscosity index VI		126	DIN ISO 2909
Flash point (COC)	°C	>100	DIN ISO 2592
Pourpoint	°C	- 25	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

29.05.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41