



RAVENOL WIV SAE 0W-30

RAVENOL WIV SAE 0W-30 is a fully synthetic fuel-saving high-performance engine oil based on the latest synthesis technology with low HTHS viscosity, developed specifically for VW and Audi gasoline and diesel engines (model year 2000 with replacement interval Extension WIV) including pump-jet engines. It enables significantly longer maintenance intervals. Excellent cold start properties through faster oil circulation system. Ensures friction losses are reduced and high oil film stability and excellent viscosity-temperature behavior.

Application Notes

RAVENOL WIV SAE 0W-30 can be used in all long-life vehicles (except for models that require a product to VW standard 503 01).

RAVENOL WIV SAE 0W-30 is not backward compatible. It should never be poured into engines of "non-WIV vehicles."

Quality Classifications

Specifications

ACEA A5/B5

Approvals

VW 503 00 / 506 00 / 506 01

Characteristic

RAVENOL WIV SAE 0W-30 offers:

- It is recommended for VW and Audi gasoline and diesel engines (model year 2000 with WIV service interval prolongation), including pump-nozzle engines.
- A special low-friction character and an excellent range by special additives.
- An excellent engine protection, even after a cold start and under stricter conditions.
- Guaranteed for maximum wear protection and engine cleanliness combined with reduced fuel consumption.
- Provides extended oil change intervals due to its exceptional product stability.
- Supports the protection of the environment through reduced emissions.

Characteristics	Unit	Data	Audit
Colour		braun	visual
Density at 20°C	kg/m ³	843	EN ISO 12185
Viscosity at 40°C	mm ² /s	55,3	DIN 51 562
Viscosity at 100°C	mm ² /s	10,1	DIN 51 562
Viscosity index VI		174	ISO 2909
Flash point (COC)	°C	220	DIN ISO 2592
Pourpoint	°C	-39	ISO 3016
TBN	mg KOH/g	10,2	DIN ISO 3771

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

22.03.2016

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41